



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 1/34, 1/36	A1	(11) International Publication Number: WO 99/36110 (43) International Publication Date: 22 July 1999 (22.07.99)
(21) International Application Number: PCT/IB99/00041 (22) International Filing Date: 14 January 1999 (14.01.99) (30) Priority Data: 0070/98 20 January 1998 (20.01.98) DK (71) Applicant (for all designated States except US): MITRA MEDICAL TECHNOLOGY AB [SE/SE]; Ideon Research Park, S-223 70 Lund (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): SANDBERG, Bengt, E., B. [SE/SE]; 18 Blomstergården, S-245 62 Hjärrup (SE). NILSSON, Rune [SE/SE]; 139 Utsättaregränden, S-226 47 Lund (SE). (74) Agent: CHAS. HUDE A/S; 33 H.C. Andersens Boulevard, DK-1553 Copenhagen V (DK).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i> <i>In English translation (filed in Danish).</i>
(54) Title: AN APPARATUS FOR USE IN CONNECTION WITH REMOVAL OF ELEMENTS, ESPECIALLY EXOGENOUS ANTIBODIES, FROM BLOOD OR PLASMA		
(57) Abstract <p>An apparatus for use in connection with removal of elements, especially exogenous antibodies, from blood or plasma flowing in an extracorporeal blood circulation system of a patient, where said apparatus comprises a container (1). This container is adapted to receive an adsorbent and comprises an inlet (15) and an outlet (16) which are adapted to be connected to an inlet conduit (19) and an outlet conduit (20), respectively, forming part of the blood circulation system. The container (1) comprises an inlet chamber (31), and adsorption chamber (32) adapted to receive the adsorbent and an outlet chamber (33). These chambers are arranged in sequence when seen in the flow direction of the blood or the plasma through the container (1) and are separated by means of filter units (11, 12) allowing passage of the blood or the plasma. The inlet (15) and the outlet (16) are arranged adjacent one another in connection with a common movable valve means (21). The valve means is adapted so has in a first position to connect the inlet (15) and the outlet (16) directly with their respective passages (28, 29) in the container wall (4) and so as in a second position to connect said inlet (15) and said outlet (16) with their respective ends of a bypass-forming channel (34) in the container wall (4). The passage (28) associated with the inlet communicates with a transfer channel (30) ending in the inlet chamber (31), whereas the passage (29) associated with the outlet (16) is open into the outlet chamber (33).</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Title: An apparatus for use in connection with removal of elements, especially exogenous antibodies, from blood or plasma.

Technical Field.

The invention relates to an apparatus for use in connection with removal of elements,
5 especially exogenous antibodies, from blood or plasma flowing in an extracorporeal blood circulation system of a patient, where said apparatus comprises a container adapted to receive an adsorbent, and where said container is provided with an inlet and an outlet adapted to be connected to an inlet conduit and an outlet conduit, respectively, forming part of the blood circulation system.

10 Background Art

It is known inter alia from WO 92/12730 to treat cancer by way of injecting antibodies containing a cytocide into the blood circulation system of a patient. From the same publication it is also known to limit the side effect of these antibodies by removing them again after a suitable period of time. In order to ensure a good result of the
15 use of antibodies, said antibodies are administered in relatively large amounts. However, only a very small portion of the antibodies, ordinarily less than 1 %, reach the cancer cells. When the remaining portion of the antibodies stay for a long period of time in the patient, said portion may involve a risk of having an injurious, damaging effect, such as when the antibodies for instance contain radioactive material.

20 It is also known to use a so-called column housing for removing the antibodies by way of adsorption. A suitable adsorbent is placed inside the column housing, said adsorbent ensuring the necessary effect during the passage of the blood. In the known systems the blood is directed through a pump and a device for separating the plasma to the column housing, whereby the blood cells are directed round the column housing
25 and returned to the plasma after said plasma has passed the column housing. The

column housing comprises a container with an inlet and an outlet in their respective ends. The inlet is connected to an inlet conduit and the outlet to an outlet conduit, and a shut-off valve is arranged in each of these conduits. A bypass conduit extends round the container, and one end of said bypass conduit is connected to the inlet conduit
5 before the shut-off valve when seen in the flowing direction of the plasma, and the other end of said bypass conduit is connected to the outlet conduit after the shut-off valve therein. The bypass conduit comprises per se at least one shut-off valve. When this column housing is used, the flow through the bypass conduit is allowed by a closing of the shut-off valves in the inlet conduit and the outlet conduit in various
10 situations, such as in connection with removal of air from the conduit system, in connection with a clogging up of the passageway through the column housing caused by for instance coagulation, and in connection with the termination of the treatment whereby a saline solution is used for expelling the plasma from the conduit system.

Such a conduit system with a column housing and a bypass conduit extending round
15 said column housing is relatively complicated and difficult to handle. In addition, it is not suited for treatment of ordinary blood, but only of blood plasma because a high risk exists of the blood coagulating in the bypass conduit while the flow therethrough is interrupted.

Brief Description of the Invention

20 The object of the invention is to provide an apparatus which presents a relatively simple structure, which is easy to operate and suited for treatment of ordinary blood.

The apparatus according to the invention is characterised in that the container comprises an inlet chamber, an adsorption chamber for receiving the adsorbent, and an outlet chamber, whereby the chambers are arranged in sequence when seen in the
25 flow direction of the blood through the container and are separated by means of filter units allowing a passage of the blood, that the inlet and the outlet are arranged adja-

cent one another on the portion of the container wall which together with a filter unit defines the outlet chamber and which is associated with a common movable valve means, where said valve means is adapted in a first position to connect the inlet and the outlet directly with their respective passages in the container wall, and where said
5 valve means is adapted in a second position to connect the inlet and the outlet with their respective ends of a bypass-forming channel in the container wall, and that the passage associated with the inlet communicates with a transfer channel ending in the inlet chamber whereas the passage associated with the outlet is open into the outlet chamber.

10 As a result, it is sufficient to operate only one valve means, and in addition the bypass channel is relatively short. The relatively short bypass channel involves a risk of coagulation of only a very small portion of blood, said portion, if any, being easily absorbed by the patient. The apparatus in question can, of course, also be used for treatment of blood plasma. By the conventional use of the apparatus, the blood flows
15 through the passage at the inlet of the container and then through the transfer channel to the inlet chamber, and subsequently the blood passes the filter unit therein and flows through the adsorption chamber containing the suitable adsorbent. From here the blood passes the second filter unit and enters the outlet chamber, whereafter it leaves said outlet chamber through the passage and flows to the outlet and is returned
20 to the patient in a conventionally known manner. When it is desired to open the bypass circulation system, the valve means is activated so as to interrupt the flow through the adsorbent and open the bypass channel.

According to the invention the valve means may be permanently connected to an inlet stub and an outlet stub with the result that said stubs are easily moved together. The
25 valve means may particularly advantageously be rotatable.

Moreover, the inlet and the outlet may according to the invention be associated with a cover accommodated on the container, said cover comprising an inner cover mem-

ber in sealing connection with the opening of the container as well as an outer cover member which is secured to the container and comprises an opening surrounding the valve means, where said valve means comprises an at least partially circumferential, radially projecting flange which is received in a corresponding recess between the two
5 cover members, stopping means being provided for stopping the rotation of the valve means at the two functional positions. The resulting embodiment is particularly simple to manufacture and operate.

In addition, the container may according to the invention be substantially axially symmetrically structured, the passage of the inlet and the associated transfer channel
10 being arranged coaxially with the axis of symmetry of the container. In this manner an embodiment is ensured which is easy both to sterilize, to fill with adsorbent, to empty of air prior to the use as well as easy to manufacture.

According to the invention the filter units may in a particular simple manner be disc-
15 shaped and provided with a porous filter cloth embedded in a carrying plastic structure.

Each filter unit may according to the invention particularly advantageously be retained in a sealing abutment against an associated circumferential abutment face on the inner wall of the container, said filter unit at the inlet chamber being retained by a separately secured bottom member and said filter unit at the outlet chamber being retained
20 by the inner cover member.

Finally the transfer channel may according to the invention be formed by a tube permanently connected to the inner cover member, said tube comprising outer circumferential grooves co-operating by way of a snapping effect with a central annular member of the carrying structure of each filter unit.

25
Brief Description of the Drawings

The invention is explained in greater detail below with reference to the accompanying drawing, in which

Fig. 1 is an axial sectional view through the apparatus according to the invention,

Fig. 2 is a top view of the same apparatus,

- 5 Fig. 3 illustrates an insertion means to be used by the sterilising and filling of the apparatus with an adsorbent, and

Fig. 4 illustrates an embodiment of a filter unit to be used in the apparatus according to the invention.

Best Mode for Carrying Out the Invention

- 10 The apparatus illustrated in Figs. 1 and 2 comprises a container designated the general reference numeral 1. This container comprises a tubular member 2 of a circular cross section and a bottom member 3 as well as a cover 4. The cover 4 comprises an inner cover member 5 and an outer cover member 6. These members are sealingly and permanently interconnected by means of suitable sealing rings 7 and 8, respectively,
- 15 as well as screw caps 9 and 10, respectively, a filter unit 11 and 12 described in greater detail below being tightened between the bottom member 3 and the inner cover member 4 as well as corresponding circumferential abutment faces 13 and 14, respectively. These abutment faces are provided on the inner side of each end of the tubular member 2 of the container 1.
- 20 An inlet 15 and an outlet 16 are provided in the cover of the container 1. The inlet 15 and the outlet 16 comprise their respective stubs 17 and 18 for connection of an inlet conduit 19 and an outlet conduit 20, respectively. Here these conduits are only indi-

cated by means of dotted lines, and they form part of a conduit system not shown in greater detail for extracorporeal circulation of blood from a patient. Each stub 17 and 18 is shaped such that they can be connected to the associated conduit by means of a Luer-coupling known per se.

5 The inlet stub 17 and the outlet stub 18 are secured in a disc-shaped valve means 21 arranged in a circular opening 22 in the outer cover member 6 and a recess 23 provided in the inner cover member 5 inside said outer cover member 6. The disc-shaped valve means 21 comprises a radially projecting circumferential flange 24 which engages a corresponding recess 25 along the periphery of the recess 23 in the inner
10 cover member 5, whereby said valve means 21 with the stubs 17 and 18 is retained in the cover 4 in such a manner that it can rotate when the stubs 17 and 18 are manually activated. A groove 26 is provided in connection with the above recess 25, said groove extending 90° around along said recess. A pin 27 engages the groove 26, said pin 27 being secured in the valve means. The said groove 26 and the pin 27 co-acting
15 therewith allow the valve means to be turned 90° forwards and backwards between two functional positions. The drawing indicates one functional position in which the inlet stub 17 and the outlet stub 18 directly oppose their respective passages 28 and 29, said passages extending directly through the inner cover member 5. A rigid transfer tube 30 is secured coaxially to the passage 28 opposite the inlet stub 17. This
20 transfer tube extends from the inner cover member 5 and coaxially through the container 1 and subsequently centrally through the filter units 11 and 12 to an opening at the chamber, viz. the inlet chamber 31, being defined between the bottom member 3 of the container 1 and the adjacent filter unit 11. A second chamber 32 is defined between the two filter units 11 and 12, said second chamber being adapted to receive
25 an adsorbent of a conventionally known type, such as an avidine agarose mixture. A third chamber, viz. an outlet chamber 33, is defined between the inner cover member 5 and the adjacent filter unit 12, said third chamber communicating directly with the outlet stub 18 through the passage 29 in the position shown of the valve means 21. The sealing connection between the valve means 21 and the inner cover member 5 is

as shown ensured by means of suitable sealing rings.

A turning of the valve means 21 into its second functional position, viz. 90° clockwise compared to Fig. 2, has the result that the inlet stub 17 and the outlet stub 18 enter a connection with their respective ends of a short channel 34 shaped in the adjacent side of the inner cover member 5.

When the stubs 17 and 18 are manually operated, the valve means 21 can thus be moved forwards and backwards between the two functional positions according to desire. The two filter units comprise a circularly cut filter cloth in form of a perforated plastic sheet, one embodiment of said filter units appearing from Fig. 4. The perforated plastic sheet allows preferably passage of particles smaller than or equal to 70 μm . This filter cloth is indicated in Fig. 1 at the reference numerals 35 and 36. In order to ensure the stability of the filter units 11 and 12, the filter cloth 35 and 36 is embedded in a plastic structure 37 resembling a wheel with spokes 38 and a central ring 39. In addition, an additional ring 40 is provided, cf. the more detailed description below. The plastic structure 37 is integrally shaped, and the filter cloth 35, 36 is removed inside the ring 39 after the moulding. The central ring 39 in the filter units 11 and 12 are dimensioned in such a manner that it co-operates with a corresponding, circumferential groove 41 and 42 on the outer side of the transfer tube 30 by way of a snapping effect. The transfer tube 30 is of a slightly smaller diameter in the area between the above grooves.

As illustrated in Fig. 2, a through liner tube 43 is mounted adjacent the periphery of the cover 4, the inner end of said liner tube sealingly engaging the said second ring 40 in the filter unit 12 adjacent the cover 4. In the state of the apparatus shown in Fig. 1, a plug 44 is provided inside the liner tube 43. During the ready-making of the apparatus this plug is replaced by a passage unit 45 with an associated stub 46, cf. Fig. 3.

The two filter units 11 and 12 are identically shaped. When a filter unit is to be used as the filter unit 12, i.e. engaging the liner tube 43 as mentioned above, the filter cloth 36 is also removed inside the ring 40.

For the ready-making of the apparatus, a sealingly closable plug 47 is also provided
5 in the bottom member 3. Likewise, an opening 48 is provided in the tubular member 2 of the container 1, said opening 48 being used at the filling of adsorbent into the chamber 32. This opening 48 is closed after the filling procedure by means of a plug 49.

The use of the apparatus illustrated in Figs. 1 and 2 implies that an initial sterilising
10 of said apparatus is performed in a conventionally known manner followed by a filling of the chamber 32 with a suitable adsorbent under sterile conditions. Subsequently, the apparatus is coupled to the inlet conduit 19 and outlet conduit 20 of the blood circulation system. While the valve means is placed in the functional position shown in Figs. 1 and 2, the blood enters through the inlet stub 17 and flows through the
15 transfer tube 30 so as to flow out in the inlet chamber 31. Then the blood continues through the filter unit 11 and through the adsorbent in the adsorption chamber 32. Thereafter the blood flows through the filter unit 12 into the outlet chamber 33 and subsequently out of said chamber through the outlet stub 16 and back to the patient in a purified state.

20 In use of the apparatus the valve means 21 is rotated according to desire into the second functional position in which the blood can flow through the bypass-forming channel 34 directly from the inlet 15 to the outlet 16 in various situations, cf. the introduction to the description.

The described apparatus is manufactured of relatively simple members by way of
25 injection moulding. The manufacture employs preferably environmentally neutral plastic materials, such as polycarbonate. The individual members are assembled by

means of relatively simple means, and the apparatus is easy to operate. After use, the apparatus is discarded in a conventionally known manner.

The invention has been described with reference to a preferred embodiment. Many modifications can be carried out without thereby deviating from the scope of the invention. The valve means may for instance be adapted to a rectilinear displacement forwards and backwards between its functional positions. In addition, some of the members, such as the inlet stub 17 and the outlet stub 18 as well as the valve means 21, may be integrally shaped. The filter units may also be manufactured in various ways.



10 As mentioned the invention is particularly suited for use in connection with removal of exogenous elements from blood or blood plasma. The invention can, of course, also be used for removing endogenous elements, such as autoantibodies, antidonor antibodies, xenoantibodies and LDL (ow Density Lipoprotein), by a suitable choice of adsorbent.


Claims

1. An apparatus for use in connection with removal of elements, especially exogenous antibodies, from blood or plasma flowing in an extracorporeal blood circulation system of a patient, where said apparatus comprises a container (1) adapted to receive
5 an adsorbent, and where said container is provided with an inlet (15) and an outlet (16) adapted to be connected to an inlet conduit (19) and an outlet conduit (20), respectively, forming part of the blood circulation system, c h a r a c t e r i s e d in, that the container (1) comprises an inlet chamber (31), an adsorption chamber (32) for receiving the adsorbent, and an outlet chamber (33), whereby the chambers are ar-
10 ranged in sequence when seen in the flow direction of the blood through the container (1) and are separated by means of filter units (11, 12) allowing a passage of the blood or the plasma, that the inlet (15) and the outlet (16) are arranged adjacent one another on the portion of the container wall (4) which together with a filter unit (12) defines the outlet chamber (33) and which is associated with a common movable valve means
15 (21), where said valve means is adapted in a first position to connect the inlet (15) and the outlet (16) directly with their respective passages (28, 29) in the container wall, and where said valve means is adapted in a second position to connect the inlet (15) and the outlet (16) with their respective ends of a bypass-forming channel (34) in the container wall (4), and that the passage (28) associated with the inlet communicates
20 with a transfer channel (30) ending in the inlet chamber (31), whereas the passage (29) associated with the outlet (16) is open into the outlet chamber (33).
2. An apparatus as claimed in claim 1, c h a r a c t e r i s e d in that the valve means (21) is permanently connected to an inlet stub (17) and an outlet stub (18).
3. An apparatus as claimed in claim 1 or 2, c h a r a c t e r i s e d in that the valve
25 means (21) is rotatable.

4. An apparatus as claimed in claim 2 or 3, c h a r a c t e r i s e d in that the inlet (15) and the outlet (16) are associated with a cover (4) provided on the container (1), said cover (4) comprising an inner cover member (5) in sealing connection with the opening of the container as well as an outer cover member (6) which is secured to the
- 5 container and comprises an opening (22) surrounding the valve means (21), where said valve means comprises an at least partially circumferential, radially projecting flange (24) which is received in a corresponding recess (25) between the two cover members (5, 6), stopping means (26, 27) being provided for stopping the rotation of the valve means (21) at the two functional positions.
- 10 5. An apparatus as claimed in claim 2, 3 or 4, c h a r a c t e r i s e d in that the container (1) is substantially axially symmetrically structured, the passage (28) of the inlet (15) and the associated transfer channel (30) being arranged coaxially to the axis of symmetry of the container.
6. An apparatus as claimed in claim 5, c h a r a c t e r i s e d in that the filter units
- 15 (11, 12) are disc-shaped and comprise a porous filter cloth (35, 36) embedded in a carrying plastic structure (37).
7. An apparatus as claimed in claim 6, c h a r a c t e r i s e d in that each filter unit (11, 12) is retained in a sealing abutment against an associated circumferential abutment face (13, 14) on the inner wall of the container (1), said filter unit (11) at the
- 20 inlet chamber (31) being retained by a separately secured bottom member (3) and said filter unit (12) at the outlet chamber (33) being retained by the inner cover member (5).
8. An apparatus as claimed in claim 6 or 7, c h a r a c t e r i s e d in that the transfer channel (30) is formed by a tube, said tube being permanently connected to the inner
- 25 cover member (5) and comprising outer circumferential grooves (41, 42) co-operating

by way of a snapping effect with a central annular member (39) of the carrying structure (37) of each filter unit (11, 12).





INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/00041

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61M 1/34, A61M 1/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2754456 A1 (ISSAUTIER ROLAND), 17 April 1998 (17.04.98), page 3, line 8 - page 10, line 34, figures 1-3 --	1-8
X	EP 0076421 A2 (GAMBRO AB), 13 April 1983 (13.04.83), page 4, line 19 - line 31; page 6, line 20 - page 7, line 26 --	1-8
X	US 5017293 A (J.M. RADOVICH ET AL.), 21 May 1991 (21.05.91), column 1, line 54 - column 2, line 36; column 4, line 40 - line 64, figure 2 --	1-3

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

24 June 1999

Date of mailing of the international search report

29 -06- 1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Lotta Gunnarsson

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/00041

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 19537688 A1 (SCITEC K.K., KAMAKURA), 2 May 1996 (02.05.96), column 5, line 48 - column 6, line 38, figure 1 --	1-4
A	WO 9212730 A1 (NILSSON, RUNE ET AL.), 6 August 1992 (06.08.92), page 9, line 2 - page 10, line 3 -- -----	6-8

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/IB 99/00041

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
FR	2754456	A1	17/04/98	NONE		
EP	0076421	A2	13/04/83	JP	58074109 A	04/05/83
				SE	427619 B,C	25/04/83
				SE	8105850 A	06/04/83
				US	4498990 A	12/02/85
US	5017293	A	21/05/91	AT	104556 T	15/05/94
				CA	2023738 A	25/02/91
				DE	69008276 D,T	24/11/94
				DK	414515 T	29/08/94
				EP	0414515 A,B	27/02/91
				ES	2055872 T	01/09/94
				JP	3109078 A	09/05/91
				US	5069788 A	03/12/91
DE	19537688	A1	02/05/96	DE	29521618 U	13/11/97
				JP	8126700 A	21/05/96
WO	9212730	A1	06/08/92	AT	178214 T	15/04/99
				CA	2100256 A	18/07/92
				DE	69116574 D	00/00/00
				DE	69228802 D	00/00/00
				EP	0567514 A,B	03/11/93
				SE	0567514 T3	
				EP	0592403 A,B	20/04/94
				FI	923778 A	21/08/92
				JP	6504542 T	26/05/94
				NO	175671 B,C	08/08/94
				SE	9100142 A	18/07/92

PUB-NO: WO009936110A1
DOCUMENT-IDENTIFIER: WO 9936110 A1
TITLE: AN APPARATUS FOR USE IN
CONNECTION WITH REMOVAL OF
ELEMENTS, ESPECIALLY
EXOGENOUS ANTIBODIES, FROM
BLOOD OR PLASMA
PUBN-DATE: July 22, 1999

INVENTOR-INFORMATION:

NAME	COUNTRY
SANDBERG, BENGT E B	SE
NILSSON, RUNE	SE

ASSIGNEE-INFORMATION:

NAME	COUNTRY
MITRA MEDICAL TECHNOLOGY AB	SE
SANDBERG BENGT E B	SE
NILSSON RUNE	SE

APPL-NO: IB09900041
APPL-DATE: January 14, 1999

PRIORITY-DATA: DK00007098A (January 20, 1998)

INT-CL (IPC): A61M001/34 , A61M001/36

EUR-CL (EPC): A61M001/36

ABSTRACT:

CHG DATE=19990902 STATUS=O>An apparatus for use in connection with removal of elements, especially exogenous antibodies, from blood or plasma flowing in an extracorporeal blood circulation system of a patient, where said apparatus comprises a container (1). This container is adapted to receive an adsorbent and comprises an inlet (15) and an outlet (16) which are adapted to be connected to an inlet conduit (19) and an outlet conduit (20), respectively, forming part of the blood circulation system. The container (1) comprises an inlet chamber (31), and adsorption chamber (32) adapted to receive the adsorbent and an outlet chamber (33). These chambers are arranged in sequence when seen in the flow direction of the blood or the plasma through the container (1) and are separated by means of filter units (11, 12) allowing passage of the blood or the plasma. The inlet (15) and the outlet (16) are arranged adjacent one another in connection with a common movable valve means (21). The valve means is adapted so has in a first position to connect the inlet (15) and the outlet (16) directly with their respective passages (28, 29) in the container wall (4) and so as in a second position to connect said inlet (15) and said outlet (16) with their respective ends of a bypass-forming channel (34) in the container wall (4). The passage (28) associated with the inlet communicates with a transfer channel (30) ending in the inlet chamber (31), whereas the passage (29) associated with the outlet (16) is open into the outlet chamber (33).